NSN 5320-01-338-4236

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-338-4236 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.010 inches and 2.030 inches **Head Style:** Err-090 **Head Height:** Between 0.112 inches and 0.127 inches Width Between Flats: Between 0.2520 inches and 0.2555 inches **Shank Diameter:** Between 0.5605 inches and 0.5615 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.829 inches and 0.864 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.245 inches and 1.255 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.562 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color code red on thread end. Phosphate fluorid surface treatment Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-338-4236

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0