

View Online at <https://aerobasegroup.com/nsn/5320-01-338-6877>

**Fastener Length:**

Between 0.492 inches and 0.512 inches

**Head Style:**

Undersized oval countersunk

**Head Height:**

Between 0.004 inches and 0.008 inches

**Shank Diameter:**

Between 0.2490 inches and 0.2495 inches

**Shank Style:**

Straight with tapered tip

**Head Major Diameter:**

Between 0.4735 inches and 0.4785 inches

**Head Minor Diameter:**

Between 0.441 inches and 0.451 inches

**Countersink Height:**

0.095 inches

**Chamfer Length:**

0.315 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 0.188 inches and 0.250 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Tail end of rivet is 45cb titanium alloy per ams 4982

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4967 assn standard single material response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-r-83459 spec.