

View Online at <https://aerobasegroup.com/nsn/5320-01-338-6878>

**Fastener Length:**

Between 1.310 inches and 1.318 inches

**Head Style:**

Tapered pan

**Head Height:**

Between 0.062 inches and 0.070 inches

**Shank Diameter:**

Between 0.162 inches and 0.164 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.250 inches and 0.272 inches

**Expansion Device:**

Serrated stem-type w

**Lubrication:**

Dry film

**Grip Length:**

Between 0.094 inches and 0.157 inches

**Shear Strength:**

95000 single pounds per square inch

**Special Features:**

Installed with double action tool

**Material:**

Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem

**Material Specification:**

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem

**Surface Treatment:**

Cadmium sleeve and chromate sleevepassivate stem

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response mechanical lockqq-p-416, type 2, cl 2 federal specification single treatment response sleeveqq-p-35 federal specification single treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0