

View Online at <https://aerobasegroup.com/nsn/5320-01-338-6880>

Fastener Length:

0.855 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.334 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.344 inches and 0.407 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Special Features:

Installed with single action tool

Material:

Iron alloy 660 mechanical lock or steel comp 316 mechanical lockiron alloy 660 sleeveiron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lockams 5737 assn standard single material response sleeveams 5737 assn standard single material response stem

Surface Treatment:

Passivate mechanical lockcadmium sleeve and chromate sleevepassivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response mechanical lockqq-p-416, type 2, cl 2 federal specification single treatment response sleeveqq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0