

View Online at <https://aerobasegroup.com/nsn/5320-01-338-6897>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.240 inches and 1.260 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.0635 inches and 0.0645 inches

**Shank Diameter:**

Between 0.1625 inches and 0.1635 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.2564 inches and 0.2612 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

Between 0.933 inches and 0.943 inches

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.164 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Identify with black dye or paint on thread end. Install using a torque controlled hex key

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Spec. 294, hi-kote 1, cagec 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0