NSN 5320-01-338-6898

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-338-6898 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.597 inches and 0.607 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.1885 inches and 0.1895 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.307 inches and 0.317 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.190 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Identify with color code black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, spec. 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

NSN 5320-01-338-6898

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0