NSN 5320-01-338-7384

Pin-rivet - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5520-01-536-7564
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.597 inches and 1.617 inches
Head Style:
Err-090
Head Height:
Between 0.078 inches and 0.088 inches
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3735 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.057 inches and 1.067 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
95000 single pounds per square inch
Special Features:
Threads are color coded black
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4928 assn standard single material response or ams 4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi kote 1, cagec 73197 mfr ref single treatment response
Thread Series Designator:

Unjf

NSN 5320-01-338-7384

Pin-rivet - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0