

View Online at <https://aerobasegroup.com/nsn/5320-01-338-8262>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.248 inches and 1.268 inches

Head Style:

Cooper's

Head Height:

Between 0.0659 inches and 0.0670 inches

Width Between Flats:

Between 0.0947 inches and 0.0967 inches

Shank Diameter:

Between 0.2485 inches and 0.2495 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5026 inches and 0.5111 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.933 inches and 0.943 inches

Thready Qty Per Inch (tpi):

28

Thread Size:

0.250 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

135.0 degrees

Special Features:

Hi kote 1 per hi shear specification 294 with threads colored orange

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0