NSN 5320-01-338-8262

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-338-8262 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.248 inches and 1.268 inches **Head Style:** Cooper's **Head Height:** Between 0.0659 inches and 0.0670 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5026 inches and 0.5111 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.933 inches and 0.943 inches Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 135.0 degrees **Special Features:** Hi kote 1 per hi shear specification 294 with threads colored orange Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5320-01-338-8262

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0