## NSN 5320-01-339-0281



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-339-0281 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.121 inches and 1.146 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3547 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.522 inches Tip Diameter: 0.3423 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.740 inches and 0.755 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.312 inches **Shear Strength:** 125000 single pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** 8-32unjc-3b thread size, 0.320 in. Lg along the longitudinal axis from the head end. 0.120 in. Slot lg. 0.060 in. Slot w located 0.260 in. From top of head to center of slot Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5320-01-339-0281

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0