## NSN 5320-01-339-0982

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-339-0982

view Online at https://aerobasegroup.com/nsn/5520-
Fastener Length:
Between 0.350 inches and 0.370 inches
Head Style:
Undersized oval countersunk
Head Height:
Between 0.002 inches and 0.006 inches
Shank Diameter:
Between 0.1630 inches and 0.1635 inches
Shank Style:
Straight with tapered tip
Head Major Diameter:
Between 0.2835 inches and 0.2885 inches
Head Minor Diameter:
Between 0.256 inches and 0.266 inches
Countersink Height:
0.051 inches
Chamfer Length:
Between 0.180 inches and 0.215 inches
Lubrication:
Cetyl alcohol
Grip Length:
Between 0.126 inches and 0.187 inches
Shear Strength:
95000 single pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Tail end of rivet is 45cb titanium alloy per ams 4982
Material:
Titanium alloy uns r56400
Material Specification:
Ams 4967 assn standard single material response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A040a0