NSN 5320-01-339-1498

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-339-1498 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.947 inches and 0.967 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.5018 inches and 0.5066 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.557 inches and 0.567 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** 100.0 degrees **Special Features:** Phosphate fluoride treat with threads colored red Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-339-1498

Pin-rivet - Page 2 of 2



Fiig:

A528u0