NSN 5320-01-339-1963

Blind Rivet - Page 1 of 1

Mil-std (military Standard):

Mil-s-6758 spec.



View Online at https://aerobasegroup.com/nsn/5320-01-339-1963 **Head Style:** Hexagon **Head Height:** 0.113 inches **Shank Diameter:** Between 0.1970 inches and 0.1990 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Expansion Device:** Break stem **Grip Length:** Between 1.407 inches and 1.469 inches Width Across Flats: Between 0.305 inches and 0.312 inches **Features Provided:** Drive nut **Special Features:** Drive nut mild steel color gold with corrosion retardent coating Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut **Material Specification:** Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nut **Surface Treatment:** Passivate sleeve and cadmium sleeve **Surface Treatment Specification:** Qq-p-416, ty2, cl2 federal specification single treatment response nut **Specification Data:** 80205-nas1669 professional/industrial association standard Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A040a0