NSN 5320-01-339-1967

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-339-1967

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.178 inches and 0.180 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.259 inches

Expansion Device:

Threaded stem

Grip Length:

Between 0.157 inches and 0.219 inches

Features Provided:

Self-locking

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or ams5639 assn standard 2nd material response sleeve or ams 5641 assn

standard 3rd material response sleeve

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification all treatment responses bolt

Specification Data:

80205-nas1754 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-5626 spec.