

View Online at <https://aerobasegroup.com/nsn/5320-01-339-1976>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.178 inches and 0.180 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.259 inches

**Expansion Device:**

Threaded stem

**Grip Length:**

Between 0.407 inches and 0.469 inches

**Features Provided:**

Self-locking

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt

**Material Specification:**

Qq-s-763 federal specification 1st material response sleeve or ams 5639 assn standard 2nd material response sleeve or ams 5641 assn standard 3rd material response sleeve

**Surface Treatment:**

Cadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification all treatment responses bolt

**Specification Data:**

80205-nas1754 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.