NSN 5320-01-339-1990



Blind Rivet - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5320-01-339-1990 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.3095 inches and 0.3115 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** 0.577 inches **Expansion Device:** Threaded stem Lubrication: Dry film or paraffin wax or cetyl alcohol **Grip Length:** Between 0.907 inches and 0.969 inches **Features Provided:** Drive nut **Hardness Rating:** 30.0 rockwell c nut and 45.0 rockwell c nut **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Drive nut steel, color coded black, with a corrosion retardent coating Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Specification Data:** 80205-nas1672 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0