

View Online at <https://aerobasegroup.com/nsn/5320-01-339-1994>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2130 inches and 0.2150 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

0.342 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Dry film or paraffin wax or cetyl alcohol

**Grip Length:**

Between 0.782 inches and 0.844 inches

**Features Provided:**

Drive nut

**Hardness Rating:**

39.0 rockwell c bolt and 43.0 rockwell c bolt

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Drive nut steel, color coded gold, with a corrosion retardent coating

**Material:**

Steel comp 4140 bolt or steel comp 8740 bolt or steel comp 4130 bolt

**Material Specification:**

Qq-a-225/9, t6 federal specification single material response nut

**Surface Treatment:**

Passivate sleeve and cadmium sleeve or passivate sleeve and cadmium sleeve and chromate sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response bolt

**Specification Data:**

80205-nas1674 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A040a0

**Mil-std (military Standard):**

Mil-s-5626 spec.