
## NSN 5320-01-339-3229

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.752 inches and 1.772 inches

## Head Style:

Err-090

#### Head Height:

Between 0.064 inches and 0.074 inches

#### Width Between Flats:

Between 0.0791 inches and 0.0806 inches

#### Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.367 inches and 0.377 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 1.432 inches and 1.442 inches

## Thready Qty Per Inch (tpi):

32

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.190 inches

## Material:

Steel comp e4340 or steel comp 4340 or steel comp 4140 or steel comp 8740

#### Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-5626 military

specification 3rd material response

#### Surface Treatment:

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5320-01-339-3229

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5000 spec.

