NSN 5320-01-339-4095

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-339-4095



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 0.468 inches and 0.488 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.1885 inches and 0.1895 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.183 inches and 0.193 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Phosphate fluoride treatment per bac 5861. Identify with orange dye or paint on thread end

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-339-4095

Pin-rivet - Page 2 of 2

Fiig: A528u0

