

View Online at <https://aerobasegroup.com/nsn/5320-01-339-8179>

Fastener Length:

0.855 inches

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.162 inches and 0.164 inches

Shank Style:

Self-plugging mechanically locked stem

Head Major Diameter:

0.334 inches

Expansion Device:

Serrated stem-type w

Lubrication:

Dry film

Grip Length:

Between 0.281 inches and 0.345 inches

Shear Strength:

95000 single pounds per square inch

Countersink Angle:

Between 98.5 degrees and 101.5 degrees

Special Features:

Installed with single action tool

Material:

Iron alloy 660 mechanical lock or steel comp 316 mechanical lock iron alloy 660 sleeve iron alloy 660 stem

Material Specification:

Ams 5737 assn standard 1st material response mechanical lock or ams 5690 assn standard 2nd material response mechanical lock
ams 5737 assn standard single material response sleeve ams 5737 assn standard single material response stem

Surface Treatment:

Passivate mechanical lock cadmium sleeve and chromate sleeve passivate stem

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response mechanical lock qq-p-416, type 2, cl 2 federal specification single treatment
response sleeve qq-p-35 federal specification single treatment response stem

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0