NSN 5320-01-340-4684

Pin-rivet - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5320-01-340-4684 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.582 inches and 0.602 inches **Head Style:** Err-090 **Head Height:** Between 0.037 inches and 0.047 inches Width Between Flats: Between 0.0635 inches and 0.0645 inches **Shank Diameter:** Between 0.1625 inches and 0.1635 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.242 inches and 0.262 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.307 inches and 0.317 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Special Features:** Color code orange on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life:

NSN 5320-01-340-4684

Pin-rivet - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A528u0