NSN 5320-01-340-5111

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5320-01-340-5111

Between 1.197 inches and 1.222 inches						
Head Style:						
Flush countersunk						
Shank Diameter:						
0.2754 inches						
Head Major Diameter:						
0.426 inches						
Tip Diameter:						
0.2603 inches						
Lubrication:						
Cetyl alcohol and dry film						
Grip Length:						
Between 0.865 inches and 0.880 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
220000 pounds per square inch						
Thread Size:						
0.250 inches						
Shear Strength:						
Shear Strength: 125000 single pounds per square inch						
125000 single pounds per square inch						
125000 single pounds per square inch Countersink Angle:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data:						
125000 single pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Steel comp xm-13 Material Specification: Ams 5629 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas172 professional/industrial association standard						

NSN 5320-01-340-5111

Pin-rivet - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A528u0