

View Online at <https://aerobasegroup.com/nsn/5320-01-340-5712>

**Head Style:**

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

**Shank Diameter:**

Between 0.2016 inches and 0.2026 inches

**Shank Style:**

Threaded self-plugging shank w/sleeve

**Head Major Diameter:**

Between 0.2966 inches and 0.3016 inches

**Expansion Device:**

Threaded stem

**Lubrication:**

Wax or cetyl alcohol or solid film

**Grip Length:**

Between 0.595 inches and 0.656 inches

**Features Provided:**

Self-locking

**Min. Tensile Strength (psi):**

1400 pounds per square inch

**Shear Strength:**

5240 double pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4130 bolt or steel comp 4140 bolt or steel comp 8740 boltsteel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nutsteel comp 303 sleeve or steel comp 304 sleeve

**Material Specification:**

Mil-s-6758 military specification 1st material response nut or mil-s-5626 military specification 2nd material response nut or mil-s-6049 military specification 3rd material response nutqq-s-763 federal specification all material responses sleeve or ams 5639 assn standard all material responses sleeve or ams 5641 assn standard all material responses sleeve

**Surface Treatment:**

Cadmium bolt and chromate boltcadmium nut and chromate nutcadmium sleeve

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response nutqq-p-416, type 1, cl 3 federal specification single treatment response sleeve

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-s-6758 spec.