# NSN 5320-01-340-6760

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-340-6760

## Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

## Shank Diameter:

Between 0.1970 inches and 0.1990 inches

## Shank Style:

Threaded self-plugging shank w/sleeve

## Head Major Diameter:

0.342 inches

#### **Expansion Device:**

Threaded stem

#### Lubrication:

Dry film or paraffin wax or cetyl alcohol

#### Grip Length:

Between 0.782 inches and 0.844 inches

#### **Features Provided:**

Drive nut

Hardness Rating:

30.0 rockwell c nut and 45.0 rockwell c nut

### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

## **Special Features:**

Drive nut steel, color coded black, with a corrosion retardent coating

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

#### Surface Treatment:

Passivate

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

#### **Specification Data:**

80205-nas1672 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A040a0