NSN 5320-01-340-6768

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-340-6768

Head Style:

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.3095 inches and 0.3115 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

0.577 inches

Expansion Device:

Threaded stem

Lubrication:

Dry film or paraffin wax or cetyl alcohol

Grip Length:

Between 0.282 inches and 0.344 inches

Features Provided:

Drive nut

Hardness Rating:

30.0 rockwell c nut and 45.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Special Features:

Drive nut steel, color coded black, with a corrosion retardent coating

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Data:

80205-nas1672 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0