NSN 5320-01-340-6773

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-340-6773

| Head Style: |
|---|
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.3725 inches and 0.3745 inches |
| Shank Style: |
| Threaded self-plugging shank w/sleeve |
| Head Major Diameter: |
| 0.696 inches |
| Expansion Device: |
| Threaded stem |
| Lubrication: |
| Dry film or paraffin wax or cetyl alcohol |
| Grip Length: |
| Between 0.220 inches and 0.281 inches |
| Features Provided: |
| Drive nut |
| Hardness Rating: |
| 30.0 rockwell c nut and 45.0 rockwell c nut |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Special Features: |
| Drive nut steel, color coded black, with a corrosion retardent coating |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single |
| material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Specification Data: |
| 80205-nas1672 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A040a0