## NSN 5320-01-340-6789

Blind Rivet - Page 1 of 1

**Demilitarization:** 

No Fiig: A040a0



View Online at https://aerobasegroup.com/nsn/5320-01-340-6789 **Head Style:** Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) **Shank Diameter:** Between 0.2740 inches and 0.2760 inches **Shank Style:** Threaded self-plugging shank w/sleeve **Head Major Diameter:** 0.463 inches **Expansion Device:** Threaded stem Lubrication: Dry film or paraffin wax or cetyl alcohol **Grip Length:** Between 0.782 inches and 0.844 inches **Features Provided:** Drive nut Hardness Rating: 30.0 rockwell c nut and 45.0 rockwell c nut **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Drive nut steel with corrosion resistant coating, color black Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Specification Data:** 80205-nas1752 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**