NSN 5320-01-340-6793

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-340-6793

Head Style:
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)
Shank Diameter:
Between 0.2740 inches and 0.2760 inches
Shank Style:
Threaded self-plugging shank w/sleeve
Head Major Diameter:
0.463 inches
Expansion Device:
Threaded stem
Lubrication:
Dry film or paraffin wax or cetyl alcohol
Grip Length:
Between 1.345 inches and 1.406 inches
Features Provided:
Drive nut
Hardness Rating:
30.0 rockwell c nut and 45.0 rockwell c nut
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Special Features:
Drive nut steel with corrosion resistant coating, color black
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Specification Data:
80205-nas1752 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig: A040a0