NSN 5320-01-340-6794

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-340-6794

Head Style:	
Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)	
Shank Diameter:	
Between 0.2740 inches and 0.2760 inches	
Shank Style:	
Threaded self-plugging shank w/sleeve	
Head Major Diameter:	
0.463 inches	
Expansion Device:	
Threaded stem	
Lubrication:	
Dry film or paraffin wax or cetyl alcohol	
Grip Length:	
Between 1.470 inches and 1.531 inches	
Features Provided:	
Drive nut	
Hardness Rating:	
30.0 rockwell c nut and 45.0 rockwell c nut	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Special Features:	
Drive nut steel with corrosion resistant coating, color black	
Material:	
Iron alloy 660	
Material Specification:	
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single	ngle
material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Specification Data:	
80205-nas1752 professional/industrial association standard	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	

Fiig:

No

A040a0