

View Online at <https://aerobasegroup.com/nsn/5320-01-341-1265>

**Fastener Length:**

0.323 inches

**Head Style:**

Universal

**Head Height:**

Between 0.054 inches and 0.064 inches

**Shank Diameter:**

Between 0.139 inches and 0.143 inches

**Shank Style:**

Self-plugging mechanically locked stem

**Head Major Diameter:**

Between 0.238 inches and 0.262 inches

**Expansion Device:**

Serrated stem-type w

**Grip Length:**

Between 0.126 inches and 0.187 inches

**Min. Tensile Strength (psi):**

325 pounds per square inch

**Shear Strength:**

325 single pounds per square inch

**Material:**

Aluminum alloy 5056 locking ringaluminum alloy 5056 sleevealuminum alloy 2024 stem

**Material Specification:**

Qq-a-430 federal specification single material response locking ringqq-a-430 federal specification single material response sleeveqq-a-430 federal specification single material response stem

**Surface Treatment:**

Anodize stem

**Surface Treatment Specification:**

Mil-a-8625 military specification 1st treatment response stem and mil-c-5541 military specification 2nd treatment response stem

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A040a0

**Mil-std (military Standard):**

Mil-a-8625 spec.