NSN 5320-01-341-1945

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-341-1945 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.740 inches and 0.760 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.075 inches and 0.090 inches **Shank Diameter:** Between 0.163 inches and 0.164 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol **Grip Length:** 0.438 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.164 inches **Shear Strength:** 95000 single pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Perhi-shear specification 294 mfr ref single treatment response **Thread Series Designator:** Unjc Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-341-1945

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0