NSN 5320-01-341-4165

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-341-4165

| Fastener Length: |
|--|
| Between 0.396 inches and 0.436 inches |
| Head Style: |
| Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer) |
| Shank Diameter: |
| Between 0.247 inches and 0.252 inches |
| Shank Style: |
| Straight |
| Head Major Diameter: |
| Between 0.472 inches and 0.480 inches |
| Expansion Device: |
| Drive stem-type h |
| Grip Length: |
| Between 0.235 inches and 0.296 inches |
| Countersink Angle: |
| Between 98.0 degrees and 102.0 degrees |
| Heat Treatment: |
| T-4 solution heat treated body |
| Material: |
| Aluminum alloy 2117 body |
| Material Specification: |
| Qq-a-430 federal specification single material response body |
| Surface Treatment: |
| Anodize body or chromate body |
| Surface Treatment Specification: |
| Mil-a-8625 military specification 1st treatment response body or mil-c-5541 military specification 2nd treatment response body |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A040a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |