

View Online at <https://aerobasegroup.com/nsn/5320-01-341-6342>

Head Style:

Hexagon

Head Height:

0.190 inches

Shank Diameter:

Between 0.3725 inches and 0.3745 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Break head

Lubrication:

Dry film or paraffin wax or cetyl alcohol

Grip Length:

Between 0.282 inches and 0.344 inches

Width Across Flats:

Between 0.491 inches and 0.500 inches

Features Provided:

Drive nut

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c nut and 43.0 rockwell c nut

Special Features:

Drive nut steel with corrosion retardent coating, color coded gold

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification 1st material response sleeve or qq-s-763 federal specification 2nd material response sleeve or ams 5639 assn standard 2nd material response sleeve

Surface Treatment:

Passivate sleeve and cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.