NSN 5320-01-341-6810

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-341-6810



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.338 inches and 1.358 inches

Head Style:

Err-090

Head Height:

Between 0.045 inches and 0.055 inches

Shank Diameter:

Between 0.1940 inches and 0.1945 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.295 inches and 0.315 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

0.948 inches

Thready Qty Per Inch (tpi):

32

Thread Size:

0.190 inches

Shear Strength:

95000 single pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Ti-shield 3, cagec 73197 mfr ref single treatment response or tiodize, type 2, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5320-01-341-6810

Pin-rivet - Page 2 of 2

Fiig: A528u0

