# NSN 5320-01-341-6812

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-341-6812



## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.287 inches and 1.307 inches

## Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

#### Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2540 inches and 0.2545 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

0.822 inches

## Thready Qty Per Inch (tpi):

28

## Thread Size:

0.250 inches

## Shear Strength:

95000 single pounds per square inch

## Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

## Surface Treatment:

Anodize

# Surface Treatment Specification:

Ti-shield 3, cagec 73197 mfr ref single treatment response or tiodize, type 2, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

# NSN 5320-01-341-6812

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

