
## NSN 5320-01-341-7542

Pin-rivet - Page 1 of 2





## Thread Class:

3a

**Thread Direction:** 

Right-hand

## Fastener Length:

Between 2.037 inches and 2.057 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.059 inches and 0.069 inches

## Width Between Flats:

Between 0.0947 inches and 0.0967 inches

## Shank Diameter:

Between 0.2540 inches and 0.2545 inches

## Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.387 inches and 0.412 inches

## Lubrication:

Solid film

## Grip Length:

Between 1.562 inches and 1.572 inches

## Thready Qty Per Inch (tpi):

28

#### Thread Size:

0.250 inches

#### Shear Strength:

132000 single pounds per square inch

#### **Special Features:**

Lf31-35-8 solid film lubricant with light blue identification on top of head

#### Material:

Cobalt comp mp-35-n

#### Material Specification:

Ams 5758 assn standard single material response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-341-7542

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

