NSN 5320-01-341-8984

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-341-8984

Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 1.496 inches and 1.521 inches
Head Style:
Flush countersunk
Shank Diameter:
0.3403 inches
Shank Style:
Pin-rivet, tapered, threaded
Head Major Diameter:
0.508 inches
Tip Diameter:
0.3202 inches
Lubrication:
Dry film and cetyl alcohol
Grip Length:
Between 1.115 inches and 1.130 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.312 inches
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Thread Series Designator:
Unif
Specification Data:
80205-nas1724 professional/industrial association standard
Shelf Life:
N/a

NSN 5320-01-341-8984

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0