NSN 5320-01-341-8985

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-341-8985 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.558 inches and 1.583 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.3403 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.508 inches Tip Diameter: 0.3189 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 1.177 inches and 1.192 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.312 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:**

80205-nas1724 professional/industrial association standard

Shelf Life:

N/a

NSN 5320-01-341-8985

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0