Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-341-9513

Fastener Length:

1.435 inches

Head Style:

Hexagon

Head Height:

0.135 inches

Shank Diameter:

Between 0.2580 inches and 0.2600 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Expansion Device:

Break stem

Grip Length:

Between 0.907 inches and 0.969 inches

Width Across Flats:

Between 0.367 inches and 0.375 inches

Features Provided:

Drive nut

Hardness Rating:

30.0 rockwell c bolt and 45.0 rockwell c bolt30.0 rockwell c nut and 45.0 rockwell c nut

Special Features:

Drive nut mild steel color black with corrosion retardent coating

Heat Treatment:

Solution heat treated boltsolution heat treated nut

Material:

Iron alloy 660

Material Specification:

Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Specification Data:

80205-nas1671 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A040a0