NSN 5320-01-341-9517

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-341-9517 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 0.760 inches and 0.785 inches **Head Style:** Flush countersunk **Shank Diameter:** 0.2624 inches **Shank Style:** Pin-rivet, tapered, threaded **Head Major Diameter:** 0.413 inches Tip Diameter: 0.2564 inches Lubrication: Dry film and cetyl alcohol **Grip Length:** Between 0.427 inches and 0.442 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch **Thread Size:** 0.250 inches **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp h11 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1724 professional/industrial association standard

Shelf Life: N/a

NSN 5320-01-341-9517

Pin-rivet - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A528u0