

View Online at <https://aerobasegroup.com/nsn/5320-01-342-0349>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.052 inches and 1.072 inches

Head Style:

Err-090

Head Height:

Between 0.055 inches and 0.065 inches

Width Between Flats:

Between 0.0791 inches and 0.0801 inches

Shank Diameter:

Between 0.1630 inches and 0.1635 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.306 inches and 0.322 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.745 inches and 0.755 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

210000 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

125000 single pounds per square inch

Special Features:

Grit blast top of heads

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Spec. 258, cagc 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0