## NSN 5320-01-342-0359

Pin-rivet - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

Fastener Length:

Between 1.597 inches and 1.617 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-342-0359

Head Style:					
Err-090					
Head Height:					
Between 0.078 inches and 0.088 inches					
Width Between Flats:					
Between 0.1582 inches and 0.1617 inches					
Shank Diameter:					
Between 0.3740 inches and 0.3745 inches					
Shank Style:					
Pin-rivet, straight, threaded					
Head Major Diameter:					
Between 0.565 inches and 0.600 inches					
Lubrication:					
Cetyl alcohol, specification 305, hi-shear corp					
Grip Length:					
Between 1.057 inches and 1.067 inches					
Thready Qty Per Inch (tpi):					
24					
Min. Tensile Strength (psi):					
220000 pounds per square inch					
Thread Size:					
0.375 inches					
Shear Strength:					
125000 single pounds per square inch					
Special Features:					
Light blue identification on top of head					
Material:					
Nickel alloy 718					
Material Specification:					
Ams 5662 assn standard single material response					
Surface Treatment:					
Passivate					
Surface Treatment Specification:					
Spec. 258, cagec 73197 mfr ref single treatment response					
Thread Series Designator:					
Unjf					

## NSN 5320-01-342-0359

Pin-rivet - Page 2 of 2



_				
c	hο	JIF.		ife:
J			_	HG.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0