# NSN 5320-01-342-2757

Solid Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-342-2757

## Fastener Length:

Between 1.115 inches and 1.135 inches

#### Head Style:

Undersized oval countersunk

# Head Height:

Between 0.004 inches and 0.006 inches

## Shank Diameter:

Between 0.249 inches and 0.252 inches

#### Shank Style:

Straight w/radius chamfered tip

#### Head Major Diameter:

Between 0.3898 inches and 0.3948 inches

#### Head Minor Diameter:

0.316 mils and 0.326 centimeters

#### **Countersink Height:**

0.060 inches

## Shear Strength:

26000 single pounds per square inch

## **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

#### Heat Treatment:

T-4 solution heat treated

## Material:

Aluminum alloy 2117

#### **Material Specification:**

Qq-a-430 federal specification single material response

#### Surface Treatment:

Anodize and chromate

#### Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

#### **Specification Data:**

80205-nas1097 professional/industrial association standard

#### Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A040a0

## Mil-std (military Standard):

Mil-a-8625 spec.