NSN 5320-01-342-3129

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-342-3129



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.218 inches and 1.238 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1562 inches and 0.1617 inches

Shank Diameter:

Between 0.3790 inches and 0.3795 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.5554 inches and 0.5604 inches

Lubrication:

Solid film and cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.683 inches and 0.693 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.375 inches

Shear Strength:

125000 single pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

Identify with light-blue paint on top of head

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-342-3129

Pin-rivet - Page 2 of 2

Fiig: A528u0

