## NSN 5320-01-342-3724

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-342-3724 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Blue **Fastener Length:** Between 0.690 inches and 0.710 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.2966 inches and 0.3016 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.558 inches and 0.568 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 95000 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 5380 double pounds per square inch **Countersink Angle:** 100.0 degrees Material: Titanium alloy uns r54520 **Material Specification:** Ams4967 mfr ref single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

\_\_

## NSN 5320-01-342-3724

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0