NSN 5320-01-342-7380

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

Between 0.823 inches and 0.843 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-342-7380

Head Style:						
Err-090						
Head Height:						
Between 0.059 inches and 0.069 inches						
Width Between Flats:						
Between 0.0947 inches and 0.0967 inches						
Shank Diameter:						
Between 0.2490 inches and 0.2495 inches						
Shank Style:						
Head Major Diameter:						
Between 0.387 inches and 0.412 inches						
Lubrication:						
Cetyl alcohol, specification 305, hi-shear corp						
Grip Length:						
Between 0.433 inches and 0.443 inches						
Thready Qty Per Inch (tpi):						
28						
Min. Tensile Strength (psi):						
220000 pounds per square inch						
Thread Size:						
0.250 inches						
Shear Strength:						
125000 single pounds per square inch						
Special Features:						
Light blue identification on top of head						
Material:						
Nickel alloy 718						
Material Specification:						
Ams 5662 assn standard single material response						
Surface Treatment:						
Passivate						
Surface Treatment Specification:						
Spec, 258, cagec 73197 mfr ref single treatment response						
Thread Series Designator:						
Unjf						

NSN 5320-01-342-7380

Pin-rivet - Page 2 of 2



	L -	11		ife	_
3	ne	п	_	пе	Ξ

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0