NSN 5320-01-342-7381

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5320-01-342-7381

Between 1.097 inches and 1.117 inches
Head Style:
Err-090
Head Height:
Between 0.078 inches and 0.088 inches
Width Between Flats:
Between 0.1582 inches and 0.1617 inches
Shank Diameter:
Between 0.3740 inches and 0.3745 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.565 inches and 0.600 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 0.557 inches and 0.567 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Thread Size:
0.375 inches
Shear Strength:
125000 single pounds per square inch
Special Features:
Light blue identification on top of head
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Spec, 258, cagec 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-342-7381

Pin-rivet - Page 2 of 2



_						
C	he	14		iŧ	0	•
J			_		ㄷ	-

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0