# NSN 5320-01-343-1020

Solid Rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-343-1020

# Fastener Length:

Between 0.240 inches and 0.260 inches

# Head Style:

Undersized oval countersunk

# Head Height:

Between 0.003 inches and 0.005 inches

# Shank Diameter:

Between 0.124 inches and 0.127 inches

#### Shank Style:

Straight w/radius chamfered tip

# Head Major Diameter:

0.1957 inches

#### Head Minor Diameter:

0.134 mils and 0.144 centimeters

# **Countersink Height:**

0.0286 inches

# Shear Strength:

33000 single pounds per square inch

# **Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

# **Special Features:**

Optional squared end

# Heat Treatment:

T-4 solution heat treated

#### Material:

Aluminum alloy 2017

# **Material Specification:**

Qq-a-430 federal specification single material response

# Surface Treatment:

Anodize or chromate

# Surface Treatment Specification:

Mil-a-8625 military specification 1st treatment response or mil-c-5541 military specification 2nd treatment response

# **Specification Data:**

80205-nas1097 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A040a0

# NSN 5320-01-343-1020

Solid Rivet - Page 2 of 2

# Mil-std (military Standard):

Mil-a-8625 spec.

