

View Online at <https://aerobasegroup.com/nsn/5320-01-343-4727>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 2.690 inches and 2.710 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.252 inches and 0.255 inches

**Shank Diameter:**

0.625 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 1.265 inches and 1.272 inches

**Lubrication:**

Cetyl alcohol

**Grip Length:**

Between 1.870 inches and 1.885 inches

**Thread Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

220000 pounds per square inch

**Thread Size:**

0.625 inches

**Shear Strength:**

7480 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Steel comp h11

**Material Specification:**

Ams6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A528u0