NSN 5320-01-343-8360

Blind Rivet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5320-01-343-8360

Head	Stv	ρ.

Flush (flat) countersunk (included angle - less than 135 degrees w or w/o chamfer)

Shank Diameter:

Between 0.2178 inches and 0.2188 inches

Shank Style:

Threaded self-plugging shank w/sleeve

Head Major Diameter:

Between 0.2966 inches and 0.3016 inches

Expansion Device:

Threaded sleeve

Lubrication:

Wax or cetyl alcohol or solid film

Grip Length:

Between 0.595 inches and 0.656 inches

Features Provided:

Self-locking

Hardness Rating:

39.0 rockwell c nut and 46.0 rockwell c nut

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 nut or steel comp 4140 nut or steel comp 8740 nut

Material Specification:

Qq-s-763 federal specification all material responses sleeve

Surface Treatment:

Cadmium sleeve

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response nut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A040a0

Mil-std (military Standard):

Mil-s-6758 spec.